



Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 14/12/2022 Revision date: 14/12/2022 Supersedes version of: 23/11/2020

Version: 3.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form Mixture

Name Hilti Zinc spray MZN-400

Product code BU Installation

Vaporizer Aerosol



1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category Professional use

Use of the substance/mixture Paint

Corrosion inhibitor

1.2.2. Uses advised against

Restrictions on use For professional use only

1.3. Details of the supplier of the safety data sheet

Supplier

Hilti (Gt. Britain) Ltd.

1 Circle Square 3 Symphony Park

GB-M1 7FS Manchester

Great Britain

T +44 161 886 1000

0800 886 100 Toll-free - F +44 161 872 1240

gbsales@hilti.com

Department issuing data specification sheet

Hilti Entwicklungsgesellschaft mbH

Hiltistraße 6

DE-86916 Kaufering

Deutschland

T +49 8191 906876

anchor.hse@hilti.com

1.4. Emergency telephone number

Emergency number Schweizerisches Toxikologisches Informationszentrum – 24h Service

+41 44 251 51 51 (international)

+44 161 886 1000

0800 886 100 Toll-free

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	NHS Direct (England and Wales) NHS 24 (Scotland)		111	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Hazardous to the aquatic environment – Acute Hazard, Category 1 H400

Hazardous to the aquatic environment – Chronic Hazard, Category 1

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

H410





Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS02

Signal word (CLP) Danger

Hazard statements (CLP) H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated. H410 - Very toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use. P260 - Do not breathe spray, vapours.

P271 - Use only outdoors or in a well-ventilated area.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Extra phrases For professional users only.

2.3. Other hazards

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

Component			
zinc (7440-66-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII		
Butane (106-97-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII		
ethyl acetate (141-78-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII		
1-methoxypropan-2-ol (107-98-2)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII		
xylene (1330-20-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII		
Solvent naphtha (petroleum), light arom. (64742-95-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII		
ethylbenzene (100-41-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII		
zinc oxide (1314-13-2)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII		

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Component			
zinc(7440-66-6)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605		





according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Component	
Butane(106-97-8)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605
ethyl acetate(141-78-6)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605
1-methoxypropan-2-ol(107-98-2)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605
xylene(1330-20-7)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605
Solvent naphtha (petroleum), light arom.(64742-95-6)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605
ethylbenzene(100-41-4)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605
zinc oxide(1314-13-2)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
zinc	CAS-No.: 7440-66-6 EC-No.: 231-175-3 EC Index-No.: 030-001-01-9	25 – 40	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Butane (Propellant gas (Aerosol)) substance with national workplace exposure limit(s) (GB)	CAS-No.: 106-97-8 EC-No.: 203-448-7 EC Index-No.: 601-004-00-0 REACH-no: 01-2119474691- 32	10 – 25	Flam. Gas 1A, H220 Press. Gas (Liq.), H280





Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ethyl acetate substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 141-78-6 EC-No.: 205-500-4 EC Index-No.: 607-022-00-5 REACH-no: 01-2119475103-	5 – 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
1-methoxypropan-2-ol substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 107-98-2 EC-No.: 203-539-1 EC Index-No.: 603-064-00-3 REACH-no: 01-2119457435- 35	5 – 10	Flam. Liq. 3, H226 STOT SE 3, H336
xylene substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 1330-20-7 EC-No.: 215-535-7 REACH-no: 01-2119488216- 32	5 – 10	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Skin Irrit. 2, H315
Solvent naphtha (petroleum), light arom.	CAS-No.: 64742-95-6 EC-No.: 265-199-0 EC Index-No.: 649-356-00-4	5 – 10	Flam. Liq. 3, H226 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
ethylbenzene substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 100-41-4 EC-No.: 202-849-4 EC Index-No.: 601-023-00-4 REACH-no: 01-2119489370- 35	3-5	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
zinc oxide	CAS-No.: 1314-13-2 EC-No.: 215-222-5 EC Index-No.: 030-013-00-7	1 – 5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general Take off immediately all contaminated clothing. Call a poison center or a doctor if you feel

unwell.

First-aid measures after inhalation Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact Gently wash with plenty of soap and water. If skin irritation or rash occurs: Get medical

advice/attention.

First-aid measures after eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid measures after ingestion Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation May cause drowsiness or dizziness.

Symptoms/effects after skin contact Irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.





Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Carbon dioxide. Foam. Dry powder. Unsuitable extinguishing media Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard Extremely flammable aerosol.

Explosion hazard Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of

burns and injuries.

Hazardous decomposition products in case of fire Toxic fumes may be released. Thermal decomposition generates: Carbon dioxide. Carbon

monoxide. Nitrogen oxides.

5.3. Advice for firefighters

Precautionary measures fire Fight fire remotely due to the risk of explosion.

Firefighting instructions DO NOT fight fire when fire reaches explosives. Evacuate area.

Protection during firefighting Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures Evacuate area. No flames, no sparks. Eliminate all sources of ignition.

6.1.1. For non-emergency personnel

Emergency procedures Ventilate spillage area. Avoid breathing spray, vapours. Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment Do not attempt to take action without suitable protective equipment. Breathing apparatus.

Emergency procedures Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Do not flush with water. Take up liquid spill into absorbent material. This material and its

container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

For further information refer to section 13. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

Additional hazards when processed Hazardous waste due to potential risk of explosion. Do not pierce or burn, even after use.

Do not eat, drink or smoke when using this product. Do not breathe vapours. Avoid contact with skin, eyes and clothing. Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

Hygiene measures Do not eat, drink or smoke when using this product. Always wash hands after handling the

product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures Proper grounding procedures to avoid static electricity should be followed.

Storage conditions Keep cool. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Keep in fireproof place.

Incompatible materials Oxidizing materials. Paper. Strong acids. Strong bases.

Storage temperature $5-25\,^{\circ}\text{C}$

Heat and ignition sources Keep away from heat and direct sunlight.





Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. National occupational exposure and biological limit values

Hilti Zinc spray MZN-400				
EU - Indicative Occupational Exposure Limit (IOEL)				
Local name	Ethylbenzene			
IOEL TWA	442 mg/m³			
IOEL TWA [ppm]	100 ppm			
IOEL STEL	884 mg/m³			
IOEL STEL [ppm]	200 ppm			
Remark	Skin			
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC			
United Kingdom - Occupational Exposure Limits				
Local name	Ethylbenzene			
WEL TWA (OEL TWA) [1]	441 mg/m³			
WEL TWA (OEL TWA) [2]	100 ppm			
WEL STEL (OEL STEL)	552 mg/m³			
WEL STEL (OEL STEL) [ppm]	125 ppm			
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)			
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE			
United Kingdom - Biological limit values				
Local name	Xylene, o-, m-, p- or mixed isomers			
BMGV	650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift			
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE			
Butane (106-97-8)				
United Kingdom - Occupational Exposure Limits				
Local name	Butane			
WEL TWA (OEL TWA) [1]	1450 mg/m³			
WEL TWA (OEL TWA) [2]	600 ppm			
WEL STEL (OEL STEL)	1810 mg/m³			
WEL STEL (OEL STEL) [ppm]	750 ppm			
Remark	Carc, (only applies if Butane contains more than 0.1% of buta-1,3-diene)			
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE			





according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ethyl acetate (141-78-6)			
EU - Indicative Occupational Exposure Limit (IOEL)			
Local name	Ethyl acetate		
IOEL TWA	734 mg/m³		
IOEL TWA [ppm]	200 ppm		
IOEL STEL	1468 mg/m³		
IOEL STEL [ppm]	400 ppm		
Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164		
United Kingdom - Occupational Exposure Limits			
Local name	Ethyl acetate		
WEL TWA (OEL TWA) [1]	734 mg/m³		
WEL TWA (OEL TWA) [2]	200 ppm		
WEL STEL (OEL STEL)	1468 mg/m³		
WEL STEL (OEL STEL) [ppm]	400 ppm		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		
1-methoxypropan-2-ol (107-98-2)			
EU - Indicative Occupational Exposure Limit (IOEL)			
Local name	1-Methoxypropanol-2		
IOEL TWA	375 mg/m³		
IOEL TWA [ppm]	100 ppm		
IOEL STEL	568 mg/m³		
IOEL STEL [ppm]	150 ppm		
Remark	Skin		
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC		
United Kingdom - Occupational Exposure Limits			
Local name	1-Methoxypropan-2-ol		
WEL TWA (OEL TWA) [1]	375 mg/m³		
WEL TWA (OEL TWA) [2]	100 ppm		
WEL STEL (OEL STEL)	560 mg/m³		
WEL STEL (OEL STEL) [ppm]	150 ppm		
Remark	Sk		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		
xylene (1330-20-7)			
EU - Indicative Occupational Exposure Limit (IOEL)			
Local name	Xylene, mixed isomers, pure		
IOEL TWA	221 mg/m³		
IOEL TWA [ppm]	50 ppm		





according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

xylene (1330-20-7)			
IOEL STEL	442 mg/m³		
IOEL STEL [ppm]	100 ppm		
Remark	Skin		
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC		
United Kingdom - Occupational Exposure Limits			
Local name	Xylene, o-,m-,p- or mixed isomers		
WEL TWA (OEL TWA) [1]	220 mg/m³ o-,m-,p- or mixed isomers		
WEL TWA (OEL TWA) [2]	50 ppm o-,m-,p- or mixed isomers		
WEL STEL (OEL STEL)	441 mg/m³ o-,m-,p- or mixed isomers		
WEL STEL (OEL STEL) [ppm]	100 ppm o-,m-,p- or mixed isomers		
Remark	Sk, BMGV		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		
United Kingdom - Biological limit values			
Local name	Xylene, o-, m-, p- or mixed isomers		
BMGV	650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		
ethylbenzene (100-41-4)			
EU - Indicative Occupational Exposure Limit (IOEL)			
Local name	Ethylbenzene		
IOEL TWA	442 mg/m³		
IOEL TWA [ppm]	100 ppm		
IOEL STEL	884 mg/m³		
IOEL STEL [ppm]	200 ppm		
Remark	Skin		
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC		
United Kingdom - Occupational Exposure Limits			
Local name	Ethylbenzene		
WEL TWA (OEL TWA) [1]	441 mg/m³		
WEL TWA (OEL TWA) [2]	100 ppm		
WEL STEL (OEL STEL)	552 mg/m³		
WEL STEL (OEL STEL) [ppm]	125 ppm		
Remark	Sk		

8.1.2. Recommended monitoring procedures

No additional information available





according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

ethyl acetate (141-78-6)			
DNEL/DMEL (Workers)			
Acute - systemic effects, inhalation	1468 mg/m³		
Acute - local effects, inhalation	1468 mg/m³		
Long-term - systemic effects, dermal	63 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	734 mg/m³		
Long-term - local effects, inhalation	734 mg/m³		
DNEL/DMEL (General population)	<u>'</u>		
Acute - systemic effects, inhalation	734 mg/m³		
Acute - local effects, inhalation	734 mg/m³		
Long-term - systemic effects,oral	4.5 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	367 mg/m³		
Long-term - systemic effects, dermal	37 mg/kg bodyweight/day		
Long-term - local effects, inhalation	367 mg/m³		
PNEC (Water)	<u>'</u>		
PNEC aqua (freshwater)	0.24 mg/l		
PNEC aqua (marine water)	0.024 mg/l		
PNEC aqua (intermittent, freshwater)	1.65 mg/l		
PNEC (Sediment)			
PNEC sediment (freshwater)	1.15 mg/kg dwt		
PNEC sediment (marine water)	0.115 mg/kg dwt		
PNEC (Soil)			
PNEC soil	0.148 mg/kg dwt		
PNEC (Oral)			
PNEC oral (secondary poisoning)	0.2 g/kg food		
PNEC (STP)			
PNEC sewage treatment plant	650 mg/l		
xylene (1330-20-7)			
DNEL/DMEL (Workers)			
Acute - systemic effects, inhalation	442 mg/m³		
Acute - local effects, inhalation	442 mg/m³		
Long-term - systemic effects, dermal	212 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	221 mg/m³		
Long-term - local effects, inhalation	221 mg/m³		
	-		





according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

xylene (1330-20-7)			
DNEL/DMEL (General population)			
Acute - systemic effects, inhalation	260 mg/m³		
Acute - local effects, inhalation	260 mg/m³		
Long-term - systemic effects,oral	12.5 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	65.3 mg/m³		
Long-term - systemic effects, dermal	125 mg/kg bodyweight/day		
Long-term - local effects, inhalation	65.3 mg/m³		
PNEC (Water)			
PNEC aqua (freshwater)	0.327 mg/l		
PNEC aqua (marine water)	0.327 mg/l		
PNEC aqua (intermittent, freshwater)	0.327 mg/l		
PNEC (Sediment)			
PNEC sediment (freshwater)	12.46 mg/kg dwt		
PNEC sediment (marine water)	12.46 mg/kg dwt		
PNEC (Soil)			
PNEC soil	2.31 mg/kg dwt		
PNEC (STP)			
PNEC sewage treatment plant	6.58 mg/l		
ethylbenzene (100-41-4)			
DNEL/DMEL (Workers)			
Acute - systemic effects, inhalation	884 mg/m³		
Acute - local effects, inhalation	884 mg/m³		
Long-term - systemic effects, inhalation	442 mg/m³		
Long-term - local effects, inhalation	442 mg/m³		
PNEC (Water)			
PNEC aqua (freshwater)	0.1 mg/l		
PNEC aqua (marine water)	0.1 mg/l		

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.





Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):







8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses. EN 166. EN 170

8.2.2.2. Skin protection

Hand protection:

In case of repeated or prolonged contact wear gloves

Hand protection					
Type Material Permeation Thickness (mm) Penetration Standard					Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	0,4		EN ISO 374

8.2.2.3. Respiratory protection

Respiratory protection:

During spraying wear suitable respiratory equipment

Respiratory protection			
Device	Filter type	Condition	Standard
Aerosol mask			

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

No additional information available No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid Colour Grey. Appearance Aerosol. Odour characteristic. Odour threshold Not available Melting point Not available Freezing point Not available Boiling point -42 °C

Flammability Extremely flammable aerosol.

Lower explosion limit 1 vol % Upper explosion limit 13.1 vol %

Flash point -25 °C (DIN EN ISO 1523)
Auto-ignition temperature 273 °C (DIN 51794)
Decomposition temperature Not available
pH Not available





Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Viscosity, kinematic 32 mm²/s (ISO 2431 (3mm))

Solubility Not available Partition coefficient n-octanol/water (Log Kow) Not available Vapour pressure 3.2 hPa (DIN EN 12) Not available Vapour pressure at 50°C Density 1.051 g/cm³ Relative density Not available Relative vapour density at 20°C Not available Particle characteristics Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

% of flammable ingredients :

9.2.2. Other safety characteristics

VOC content 611.4 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

No additional information available

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Heat. Sparks. Open flame. Direct sunlight. Overheating.

10.5. Incompatible materials

Oxidizing agents and bases.

10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)

Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (dermal)

Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (inhalation)

Not classified (Based on available data, the classification criteria are not met)

zinc (7440-66-6)		
LD50 oral rat	> 2000 mg/kg (OECD 401 method)	
LC50 Inhalation - Rat (Dust/Mist)	> 5.41 mg/l/4h no mortalities;(OECD 403 method)	
Butane (106-97-8)		
LC50 Inhalation - Rat [ppm]	> 800000 ppm/4h	
ethyl acetate (141-78-6)		
LD50 oral rat	> 2000 mg/kg ((OECD 401 method))	
LD50 dermal rabbit	> 20000 mg/kg (male)	
LC50 Inhalation - Rat [ppm]	> 6000 ppm (6 h)	





according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

1-methoxypropan-2-ol (107-98-2)			
LD50 oral rat	4016 mg/kg bodyweight		
LD50 dermal rat	> 2000 mg/kg bodyweight		
xylene (1330-20-7)			
LD50 oral rat	3523 mg/kg (male; EU Method B.1)		
LD50 dermal rabbit	> 5000 mg/kg		
LC50 Inhalation - Rat (Vapours)	29.091 mg/l/4h (male; EU Method B.2)		
Solvent naphtha (petroleum), light arom. (64742-95-6)			
LD50 oral rat	> 6800 mg/kg bodyweight		
LD50 dermal rabbit	> 3400 mg/kg bodyweight		
LC50 Inhalation - Rat (Vapours)	> 10.2 mg/l/4h		
ethylbenzene (100-41-4)	<u> </u>		
LD50 oral rat	≈ 3500 mg/kg bodyweight		
LD50 dermal rabbit	17.8 ml/kg (male)		
LC50 Inhalation - Rat (Vapours)	17.8 mg/l/4h		
zinc oxide (1314-13-2)			
LD50 oral rat	> 5000 mg/kg bodyweight (OECD 401 method)		
LD50 dermal rat	,		
	> 2000 mg/kg bodyweight (OECD 402 method)		
LC50 Inhalation - Rat (Dust/Mist)	> 5.7 mg/l/4h (OECD 403 method)No mortality with the given dose		
	Not classified		
	Not classified		
• •	Not classified (Based on available data, the classification criteria are not met)		
· .	Not classified (Based on available data, the classification criteria are not met)		
	Not classified (Based on available data, the classification criteria are not met)		
Reproductive toxicity	Not classified (Based on available data, the classification criteria are not met)		
STOT-single exposure	Not classified		
ethyl acetate (141-78-6)			
STOT-single exposure	May cause drowsiness or dizziness.		
1-methoxypropan-2-ol (107-98-2)			
STOT-single exposure	May cause drowsiness or dizziness.		
Solvent naphtha (petroleum), light arom. (64742-95-6	5)		
STOT-single exposure	May cause drowsiness or dizziness.		
STOT-repeated exposure	Not classified (Based on available data, the classification criteria are not met)		
STOT-repeated exposure ethylbenzene (100-41-4)	Not classified (Based on available data, the classification criteria are not met)		
	Not classified (Based on available data, the classification criteria are not met) May cause damage to organs (hearing organs) through prolonged or repeated exposure.		
ethylbenzene (100-41-4) STOT-repeated exposure			
ethylbenzene (100-41-4) STOT-repeated exposure	May cause damage to organs (hearing organs) through prolonged or repeated exposure.		
ethylbenzene (100-41-4) STOT-repeated exposure Aspiration hazard	May cause damage to organs (hearing organs) through prolonged or repeated exposure.		





Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

OLOTTON 12: Loological information			
12.1. Toxicity			
Hazardous to the aquatic environment, short–term (acute)	Very toxic to aquatic life. (Based on available data, the classification criteria are not met)		
Hazardous to the aquatic environment, long-term (chronic)	Very toxic to aquatic life with long lasting effects. (Based on available data, the classification criteria are not met)		
zinc (7440-66-6)			
LC50 - Fish [1]	169 μg/l (96h; Oncorrhynchus Mykiss)		
EC50 - Crustacea [1]	< 0.1 μg/l (48h; Ceriodaphnia dubia)		
NOEC chronic fish	26 μg/L (30 d; Jordanella floridae)		
NOEC chronic crustacea	48 μg/L (21d; Daphnia magna; (OECD 211 method))		
Butane (106-97-8)			
LC50 - Fish [1]	24 – 148 mg/l (Quantitative structure-activity relationship (QSAR))		
EC50 - Crustacea [1]	7 – 70 mg/l (Quantitative structure-activity relationship (QSAR))		
EC50 72h - Algae [1]	7 – 17 mg/l (Quantitative structure-activity relationship (QSAR))		
ethyl acetate (141-78-6)			
LC50 - Fish [1]	220 mg/l (96 h; Pimephales promelas; US EPA E03-05)		
NOEC chronic crustacea	2.4 mg/l (21 d; Daphnia magna; (OECD 211 method))		
NOEC chronic algae	> 100 mg/l (72 h; Desmodesmus subspicatus; (OECD 201 method))		
1-methoxypropan-2-ol (107-98-2)			
LC50 - Fish [1]	6812 mg/l (96 h; Leuciscus idus; DIN 38 412, part L15)		
EC50 - Crustacea [1]	> 100 mg/l (48 h; Daphnia magna)		
xylene (1330-20-7)			
LC50 - Fish [1]	2.6 mg/l (96 h; Oncorhynchus mykiss; (OECD 203 method))		
EC50 - Crustacea [1]	2.2 mg/l (24 h; Daphnia magna; (OECD 202 method))		
ErC50 algae	2.2 mg/l (72 h; Pseudokirchneriella subcapitata; (OECD 201 method))		
NOEC chronic fish	> 1.3 mg/l (56 d; Oncorhynchus mykiss)		
NOEC chronic crustacea	0.96 mg/l (7 d; Ceriodaphnia dubia; US EPA 600/4-91-003)		
Solvent naphtha (petroleum), light arom. (64742-9	5-6)		
LC50 - Fish [1]	8.2 mg/l (96h; Pimephales promelas; EPA 66013-75-009)		
EC50 - Crustacea [1]	4.5 mg/l (48h; Daphnia magna; (OECD 202 method))		
ErC50 algae	3.7 mg/l (96h; Pseudokirchneriella subcapitata; (OECD 201 method))		
NOEC chronic crustacea	2.6 mg/l (21d; Daphnia magna; (OECD 211 method))		
ethylbenzene (100-41-4)			
LC50 - Fish [1]	5.1 mg/l (96h; Menidia menidia)		





according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ethylbenzene (100-41-4)	
LC50 - Fish [2]	4.2 mg/l (96; Oncorhynchus mykiss (Rainbow trout); (OECD 203 method))
EC50 - Crustacea [1]	1.8 – 2.4 mg/l (48h; Daphnia magna)
EC50 72h - Algae [1]	4.9 mg/l (72h; Skeletonema costatum)
EC50 72h - Algae [2]	5.2 mg/l (72h; Pseudokirchnerella subcapitata)
ErC50 algae	4.9 mg/l (72h; Skeletonema costatum)
NOEC chronic crustacea	0.96 mg/l (7d; Ceriodaphnia dubia)
zinc oxide (1314-13-2)	
LC50 - Fish [1]	1.55 mg/l (96 h; Danio rerio)
EC50 - Crustacea [1]	1 mg/l (48 h; Daphnia magna; (OECD 202 method))
EC50 72h - Algae [1]	0.136 mg/l (72 h; Pseudokirchneriella subcapitata; (OECD 201 method))
NOEC chronic fish	0.039 mg/l (30 d; Oncorhynchus mykiss; (OECD 215 method); <tx:kft_read-across>)</tx:kft_read-across>
NOEC chronic crustacea	0.04 mg/l (21 d; Daphnia magna; (OECD 211 method); <tx:kft_read-across>)</tx:kft_read-across>
NOEC chronic algae	0.01 mg/l (4 d; Dunaliella tertiolecta)

12.2. Persistence and degradability

zinc (7440-66-6)		
Persistence and degradability	Not applicable for inorganic products.	
ethyl acetate (141-78-6)		
Persistence and degradability	Readily biodegradable.	
Biodegradation	≈ 69 % (20 d)	
1-methoxypropan-2-ol (107-98-2)		
Persistence and degradability	Readily biodegradable.	
Biodegradation	96 % (28 d; (OECD 301E method))	
xylene (1330-20-7)		
Persistence and degradability	Readily biodegradable.	
Biodegradation	87.8 % (28 d; (OECD 301F method))	
ethylbenzene (100-41-4)		
Persistence and degradability	Readily biodegradable.	
Biodegradation	70 – 80 % (28d; ISO 14593-CO2-Headspace Test)	
zinc oxide (1314-13-2)		
Persistence and degradability	Not applicable for inorganic products.	

12.3. Bioaccumulative potential

zinc (7440-66-6)		
Bioaccumulative potential Bioaccumulation unlikely.		
ethyl acetate (141-78-6)		
ethyl acetate (141-78-6)		





Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ethyl acetate (141-78-6)		
Bioaccumulative potential	Bioaccumulation unlikely.	
1-methoxypropan-2-ol (107-98-2)		
Partition coefficient n-octanol/water (Log Kow)	0.37 (20 °C)	
Bioaccumulative potential	Bioaccumulation unlikely.	
xylene (1330-20-7)		
Bioconcentration factor (BCF REACH)	< 25.9	
Bioaccumulative potential	No additional information available.	
zinc oxide (1314-13-2)		
Bioaccumulative potential	Bioaccumulation unlikely.	

12.4. Mobility in soil

1-methoxypropan-2-ol (107-98-2)		
Surface tension	70.7 mN/m (1 g/L; 20°C)	
xylene (1330-20-7)		
Surface tension	28 – 29.8 mN/m	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.73	
ethylbenzene (100-41-4)		
Surface tension	71.2 N/m (23 °C)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.12 (calculated)	

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)

Waste treatment methods

Product/Packaging disposal recommendations

Additional information

European List of Waste (LoW) code

Disposal must be done according to official regulations.

Dispose of contents/container in accordance with licensed collector's sorting instructions.

Container under pressure. Do not drill or burn even after use.

Flammable vapours may accumulate in the container.

14 06 03* - other solvents and solvent mixtures

16 05 04* - gases in pressure containers (including halons) containing dangerous

substances

15 01 04 - metallic packaging





Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

HP Code

HP3 - "Flammable:"

- flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
- flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
- flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
- flammable gaseous waste: gaseous waste which is flammable in air at 20 $^{\circ}\text{C}$ and a standard pressure of 101.3 kPa;
- water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
- other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.

HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / RID

ADR	IMDG	IATA	RID	
14.1. UN number or ID number				
UN 1950	UN 1950	UN 1950	UN 1950	
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	
Transport document description				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	
14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1	
***************************************	***************************************	***************************************	1 1 1 2 2	
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	
Environmentally hazardous substances derogation applies (quantity of liquids ≤ 5 litres or net mass of solids ≤ 5 kg). The environmentally hazardous substance mark is therefore not required, as stated in the ADR regulation, section 5.2.1.8.1.				

14.6. Special precautions for user

No supplementary information available

Overland transport

Classification code (ADR)

Special provisions (ADR) 190, 327, 344, 625

Limited quantities (ADR) 11
Excepted quantities (ADR) E0





Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Packing instructions (ADR) P207, LP200 Special packing provisions (ADR) PP87, RR6, L2

Transport category (ADR) 2
Special provisions for carriage - Packages (ADR) V14
Special provisions for carriage - Loading, unloading CV9, CV12

and handling (ADR)

Special provisions for carriage - Operation (ADR) S2
Tunnel restriction code (ADR) D

Transport by sea

Special provisions (IMDG) 63, 190, 277, 327, 344, 381, 959

 Limited quantities (IMDG)
 SP277

 Excepted quantities (IMDG)
 E0

 Packing instructions (IMDG)
 P207, LP200

 Special packing provisions (IMDG)
 PP87, L2

EmS-No. (Fire)

EmS-No. (Spillage)

Stowage category (IMDG)

From the special packing provisions (IMDG)

From the special packing provisions (IMDG)

From the special packing provisions (IMDG)

Air transport

PCA Excepted quantities (IATA) E0
PCA Limited quantities (IATA) Y203
PCA limited quantity max net quantity (IATA) 30kgG
PCA packing instructions (IATA) 203
PCA max net quantity (IATA) 75kg
CAO packing instructions (IATA) 203
CAO max net quantity (IATA) 150kg

Special provisions (IATA) A145, A167, A802

ERG code (IATA) 10L

Rail transport

Classification code (RID) 5F

Special provisions (RID) 190, 327, 344, 625

 Limited quantities (RID)
 1L

 Excepted quantities (RID)
 E0

 Packing instructions (RID)
 P207, LP200

 Special packing provisions (RID)
 PP87, RR6, L2

Mixed packing provisions (RID) MP9
Transport category (RID) 2
Special provisions for carriage -Packages (RID) W14
Special provisions for carriage - Loading, unloading CW9, CW12

and handling (RID)

Colis express (express parcels) (RID) CE2
Hazard identification number (RID) 23

14.7. Maritime transport in bulk according to IMO instruments

Not applicable





Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	Hilti Zinc spray MZN-400; ethyl acetate; 1- methoxypropan-2-ol; xylene; Solvent naphtha (petroleum), light arom.; ethylbenzene	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	Hilti Zinc spray MZN-400; ethyl acetate; 1- methoxypropan-2-ol; xylene; Solvent naphtha (petroleum), light arom.; ethylbenzene	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	Hilti Zinc spray MZN-400; Solvent naphtha (petroleum), light arom.; ethylbenzene	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	propane; Butane; ethyl acetate; 1- methoxypropan-2-ol; xylene; Solvent naphtha (petroleum), light arom.; ethylbenzene	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

VOC content 611.4 g/l





Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Seveso Directive (Disaster Risk Reduction)

Seveso III Part I (Categories of dangerous substances)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
P3a FLAMMABLE AEROSOLS 'Flammable' aerosols Category 1 or 2, containing flammable gases Category 1 or 2 or flammable liquids Category 1	150	500
E1 Hazardous to the Aquatic Environment in Category Acute 1 or Chronic 1	100	200

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Indication of changes				
Section	Changed item	Change	Comments	
	General	Modified	SDS EU format according to COMMISSION REGULATION (EU) 2020/878	
9	Physical and chemical properties	Modified		
11	Toxicological information	Modified		
12.1	Ecotoxicological information	Modified		
15	Regulatory information	Added		

Abbreviations and acronyms:		
CAS-No.	Chemical Abstract Service number	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008	
DNEL	Derived-No Effect Level	
EC50	Median effective concentration	
ED	Endocrine disrupting properties	
EC-No.	European Community number	
EN	European Standard	





according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:		
IATA	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
IOELV	Indicative Occupational Exposure Limit Value	
LC50	Median lethal concentration	
LD50	Median lethal dose	
NOEC	No-Observed Effect Concentration	
OECD	Organisation for Economic Co-operation and Development	
N.O.S.	Not Otherwise Specified	
OEL	Occupational Exposure Limit	
PBT	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail	
SDS	Safety Data Sheet	
STP	Sewage treatment plant	
TLM	Median Tolerance Limit	
TRGS	Technical Rules for Hazardous Substances	
VOC	Volatile Organic Compounds	
WGK	Water Hazard Class	
vPvB	Very Persistent and Very Bioaccumulative	
NOAEL	No-Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
LOAEL	Lowest Observed Adverse Effect Level	

Data sources

Source: European Chemicals Agency, http://echa.europa.eu/. manufacturer.

Full text of H- and EUH-statements:		
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4	
Aerosol 1	Aerosol, Category 1	
Aquatic Acute 1	Hazardous to the aquatic environment —Acute Hazard, Category 1	
Aquatic Chronic 1	Hazardous to the aquatic environment —Chronic Hazard, Category 1	
Aquatic Chronic 2	Hazardous to the aquatic environment -Chronic Hazard, Category 2	
Aquatic Chronic 3	Hazardous to the aquatic environment -Chronic Hazard, Category 3	
Asp. Tox. 1	Aspiration hazard, Category 1	
EUH066	Repeated exposure may cause skin dryness or cracking.	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	





according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:		
Flam. Gas 1A	Flammable gases, Category 1A	
Flam. Liq. 2	Flammable liquids, Category 2	
Flam. Liq. 3	Flammable liquids, Category 3	
H220	Extremely flammable gas.	
H222	Extremely flammable aerosol.	
H225	Highly flammable liquid and vapour.	
H226	Flammable liquid and vapour.	
H229	Pressurised container: May burst if heated.	
H280	Contains gas under pressure; may explode if heated.	
H304	May be fatal if swallowed and enters airways.	
H312	Harmful in contact with skin.	
H315	Causes skin irritation.	
H319	Causes serious eye irritation.	
H332	Harmful if inhaled.	
H336	May cause drowsiness or dizziness.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
Press. Gas (Liq.)	Gases under pressure : Liquefied gas	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
STOT RE 2	Specific target organ toxicity -Repeated exposure, Category 2	
STOT SE 3	Specific target organ toxicity -Single exposure, Category 3, Narcosis	

SDS EU Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.